

11

11



□□&□□

MOQ	5
	2500/
	A4

品名	ステンレス鋼板
仕様	T / T幅30mm標準規格L / C
寸法	幅25-35mm
重量	標準 20 GP標準規格18mm 40 GP標準規格22mm



品名

仕様

標準規格
 2000mm標準規格
 2000mm標準規格



品名



TEST REPORT

No. : QZN1603012602M.
Date : Apr 05, 2016
Page: 1 of 2

CUSTOMER NAME: HARBIN DONGXING ALUMINUM CO., LTD.
ADDRESS: NO.1 TIANFU ROAD, XINJIA INDUSTRIAL AREA, PINGFANG DISTRICT, HARBIN, CHINA 150066

The following sample(s) was/were submitted and identified on behalf of the client as:
Sample Name : 5052 ALLOY IN 3MM THICKNESS
SGS Ref. No. : QZN1603012563PC
Date of Receipt : Mar 30, 2016
Testing Start Date : Mar 30, 2016
Testing End Date : Apr 05, 2016
Test result(s) : For further details, please refer to the following page(s)

Signed for:
SGS-CTC Standards Technical
Services Co., Ltd. QC Branch Testing
Center
Shiying Chen
Authorized signatory



Member of the SGS Group since 2003



TEST REPORT

No. : QZN1603012602M.
Date : Apr 05, 2016
Page: 2 of 2

Tensile Test


Test Method: ASTM B209-14 & ASTM A213-14

Test Item	Specimen Size	Tensile strength, R _m (MPa)	Yield strength, R _{0.2} (MPa)	Elongation after fracture, A ₅ (%)	Gr.
ASTM B209-14 5052 H32	-	315 (315-320) (315-320)	155 (155-160) (155-160)	17 (17-18) (17-18)	-
Result	Rectangular specimen	315	155	17	Plate

Note 1: 1 is sample thickness, in.

2. The results comply with the requirement of ASTM B209-14 type 5052 H32.

Original Sample Photo



End of report



Member of the SGS Group since 2003



Amber Zheng

- Position: Sales Manager
- Tel: 0086-0451-87105377 0086-13766825059
- Email: amber@aludongxing.com
- SKYPE: amberamber796
- Trademanager: cnaludongxing
- QQ: 2851851713