

1.Base

Material	Aluminum
Temp	8011,1100,3102,1030B
Temp	H22 / H26
Temp	0.08-0.2mm +/- 5%
Temp	200mm-1900mm +/- 1.0mm
Temp	Silver Plain&Anodized
Temp	FDA ISO9001 2000 Mill
Temp	Standard
Temp	2000/
Temp	T / Tolerance LC
Temp	30
Temp	Standard
Temp	Standard



2. Material Properties

Material; Properties; Mechanical Properties



3. Dimensions

30 Dimensions

Standard Dimensions



4. Packaging

Standard 2000 Standard sheet. Our 30 Standard Packaging



5.Certificate

Standard ISO FDA



6.FAQ

□ □ □ □ □ □ □ □ □ □ □

□□□□□□□□5-10□ □□□□□□□□□□□□□□□□45-60□□

11 12 13 14 15

□ □ □ □ □ □ □ □ □ □

□□□□30□T / T□□□□□ □□□□L / C

11/11

□□□□□□□□□□100□ □□□□□□□□□□□□

Two rows of empty boxes for writing answers. Each row contains 15 boxes, with a gap between the 8th and 9th boxes in each row.

□ □ □ □

Cala Zhang

□ □ □ □ □ □ □ □ □ □

☎☎☎☎86-0451-87105399 WhatsApp☎☎+ 0086-15776907228

QQ:2851851712 Skype:cala.zhang