




000	8011 000 00 0000 0 0
00	1000 ~ 8000 000
00	O-H112
00	0.006-0.2mm
0	200-1960 mm
000	76/152 mm 00 000 00
00	00 / 0000 / 00
00	PE / PVDF.
00	00 00 E ≤0.6 %.
00	00 000 00
00 00	PE≥18um; PVDF≥25um; (00 00) ≥2HB
00	≥1 00
0 000	000 00 000 00 000 000000 (50KG / CM, ASTM-D-2794 : 1993)
00 00 000 00 00	≥100
0000	000 0000 10000 00
MOQ	3 0
00	GB / T 3880-2006, Q / Q 141-2004, ASTM, JIS, EN
00	ISO9001, SGS, ROHS, FDA, TUV





□□ □□ □□ : □□□ □□ □□ 35-45 □

1. 2. 3.

1. □□ □□ □□ 2. □□□□ 3. □□□ □□

東興 東興 東興 東興

[illegible]



□□□□

□□□ □□□□ □□□ □ □□ □□□ □□□□ □□□ □□ □ □□ □□□□□. □□ □□□□□, □□ □□□□ □ □□□ □□ □□□□ □□□□ □□□ □ □□ □□ □□□□□ □□□□ □□□□□.

✕
✕