

Specification

Product Name	Aluminum foil for lamination
Alloy	1000 to 8000 series
Temper	O-H112
Thickness	0.006-0.2mm
Width	200-1960 mm
ID	76/152 mm or as your require
Core	Paper/Aluminum/Steel
Coated	PE/PVDF.
Color	color difference delta E&le within 0.6.
Goss	according to customer request
Coating thickness	PE≥18um; PVDF≥25um;(Pencil hardness)≥2HB
Adhesion	≥1grade
The impact resistance	don't drop paint, no cracks(50KG/CM,ASTMD-2794:1993)
Resistance to methyl ethyl ketone	≥100
Abrasion resistance	≥10000 without any change
MOQ	3 tons
Standard	GB/T 3880-2006, Q/Q 141-2004, ASTM, JIS, EN
Certification	ISO9001,SGS, ROHS,FDA,TUV





Application



Packing & Delivery

Packing Details : Standard export package

Delivery Details : 35-45 days after receiving the prepayment



1. Special logistics packaging 2. Wooden cases 3. Complete package



1. Special logistics packaging 2.process 3. Complete package

Products structure



Our factory

Harbin Dongxing Aluminum Co., Ltd

It was established in 2000, which is a professional cooperation that specialized in manufacturing aluminum alloys and deep-processing with aluminum materials. We can manufacture full series of aluminum alloy materials; mainly include aluminum plate/sheet, coil/strip, foil, etc, altogether 18 categories, 260 alloys, more than 4500 varieties and 20000 sizes.





Contact us

We have an efficient sales and technical team to provide customers with comprehensive technical support. In product upgrades, technical updates and customers to make progress together to provide customers with aluminum alloy applications on the solution.

